



LTE ROUTER RUT240



4G/LTE mobil router til en fordelagtig pris, med en bred vifte af funktioner og kompakt størrelse.



Kraftfuld

- 4G/LTE
- WiFi
- To Ethernet porte (1x LAN, 1x WAN, konfigurerbar)
- OpenVPN kryptering



Pålidelig

- Stort temperaturspænd (-40°C til +75°C)
- DIN-skinne og vægmontering (holdere sælges separat)
- Modstandsdygtig over for vibrationer
- WAN fallback



Alsidig

- Kompakt
- Letvægt (125 g)
- Lavt strømforbrug (maks. 5 W)



Omkostningseffektiv

- Tilbehør medfølger
- Hurtig implementering



[Snak med en af vores konsulenter om dine router behov...](#) ➤



Tekniske Specifikationer

Mobile communications

LTE 800/900/1800/2100/2600 MHz
 LTE max. 150 Mbit/s Download / 50 Mbit/s Upload
 UMTS/HSPA+ 900/2100 MHz
 HSDPA max. 42,2 Mbit/s Download / 5,76 Mbit/s Upload
 GPRS/EDGE 900/1800 MHz
 GPRS/EDGE max. 236,8 kbit/s Download / 236,8 kbit/s Upload

WiFi

IEEE 802.11 b/g/n (2,4 GHz)
 WEP/WPA/WPA2
 encryption 128bit (max. 150
 Mbit/s)

LED

1 x Power on
 3 x Mobile connection status
 5 x Mobile signal strength
 2 x WAN/LAN activity

Processor

400 MHz MIPS CPU
 64 MB RAM

Ethernet

2 port switch (1 x LAN, 1 x WAN, configurable)
 10/100 Mbit/s BASE-T
 Auto MDI/MDIX

OpenVPN

Mode: Client, Server
 Protocol: UDP, TCP
 LZO compression

Accessories included

1 230VAC plug-in power supply (op. temperature: 0° to
 +40°C) 2 Mobile antennas (with hinge)
 1 WiFi antenna (with hinge)
 1 Ethernet cable

Optional: DIN rail holder, Wall holder,
 DIN rail power supply, Antennas

Firmware

User-friendly web GUI
 Signal strength readout (LEDs and on the web login page)
 Firewall with zone policies, MAC filter
 Auto reboot (ping check, schedule)
 DHCP server (with static assignment via MAC)
 PPPoE and DHCP client for DSL/Cable/Sat connection WAN
 failover
 SMS functions
 (sending/receiving, forwarding, management/configuration)
 NTP Client (configurable synchronisation interval)
 Event logging (with SMS/E-Mail/FTP alerts)
 Customized shell scripts
 Configuration profiles
 SSH access

Ports

Power supply (4 pin socket)
 2 x Ethernet (RJ-45)
 Mobile: 2 x SMA (Main, Aux for Rx-Diversity/MIMO)
 WiFi: 1 x RP-SMA
 SIM slots: 1 x 2FF (external)

Power Supply

9 - 30 V DC, max. 6,5W

Dimensions

L x W x H 74 x 83 x 25 mm (w/o DIN rail holder) 125 g
 (w/o DIN rail holder)
 DIN rail mounting optionally on side or rear side

Operating Conditions

Temperature (operating): -40°C to +75°C
 Humidity (operating): 10 % to 90 % (non-condensing)