



LTE ROUTER RUT955



RUT955 er optimeret til 4G/LTE-mobilnetværk og opfylder de nyeste industristandarder.



Plug and Play

- Mulighed for fast privat IP
- Klar-til-brug pre-konfiguration
- Nem installation



Mange tilslutningsmuligheder

- 4 Ethernetporte (3x LAN, 1x WAN, konfigurerbar)
- WiFi modul
- Tilsluttes terminaludstyr via Ethernet eller WiFi
- Tilslut 3-4 LAN-enheder



Stor fleksibilitet

- Backup løsning til DSL (WAN fallback)
- Dual-SIM router
- Høj sikkerhed med krypteret datakommunikation via OpenVPN-teknologi



Industriel kvalitet

- Driftstemperatur fra -40°C til +70°C (Grænseværdi luftfugtighed: 10% - 90%)



[Snak med en af vores konsulenter om dine router behov...](#) ➔



Tekniske Specifikationer

Mobile communications

LTE 800/900/1800/2100/2600 MHz
 LTE max. 150 Mbit/s download / 50 Mbit/s upload
 UMTS/HSPA+ 900/2100 MHz
 HSDPA max. 42,2 Mbit/s download / 5,76 Mbit/s upload
 GPRS/EDGE 900/1800 MHz
 GPRS/EDGE max. 236,8 kbit/s download / 236,8 kbit/s upload

WiFi

IEEE 802.11 b/g/n (2,4 GHz)
 WEP/WPA/WPA2 encryption
 2T2R (max. 300 Mbit/s)

LED indicators

1 x Power on
 1 x Mobile connection
 status 5 x Mobile signal strength
 5 x WAN/LAN activity

Processor

560 MHz MIPS CPU
 128 MB RAM

Ethernet

4 port switch (3 x LAN, 1 x WAN, configurable) 10/100 Mbit/s BASE-T
 Auto MDI/MDIX

OpenVPN

Mode: Client, Server
 Protocol: UDP, TCP
 LZO compression

Accessories included

1 230VAC plug-in power supply (op. temperature: 0° to +40°C)
 2 Mobile antennas (magnetic, 3 m cable)
 2 WiFi antennas (magnetic, 1.5 m cable)
 1 GPS antenna (adhesive, 3 m cable)
 1 Ethernet cable (1.5 m)

Optional: DIN rail holder, wall holder,
 DIN rail power supply, antennas

Firmware

User-friendly web GUI
 Signal strength readout (LEDs and on the web login page)
 Firewall with zone policies, MAC filter
 Auto reboot (ping check, schedule)
 DHCP server (with static assignment via MAC)
 PPPoE and DHCP client for DSL/Cable/Sat connection
 Dual SIM, WAN failover
 SMS functions
 (sending/receiving, forwarding, management/configuration)
 NTP Client (configurable synchronization interval)
 Event logging (with SMS/E-Mail/FTP alerts)
 Customized shell scripts
 Configuration profiles
 SSH access

Ports

Power supply (4-pin socket)
 4 x Ethernet (RJ-45)
 Mobile: 2 x SMA (main, aux for Rx diversity/MIMO)
 WLAN: 2 x RP-SMA
 SIM slots: 2 x 2FF (external).

Power Supply

9 - 30 V DC, max. 7W

Dimensions

L x W x H 100 x 110 x 50 mm
 (w/o DIN rail holder)
 287 g (w/o DIN rail holder)

Operating Conditions

Temperature (operating): -40°C to +75°C
 Humidity (operating): 10 % to 90 % (non-condensing)